



SEC:A-A

P1	P2
1 BLACK	1
2 RED	2
3 GREEN	3
4 YELLOW	4



**Note:**

- Material: Housing-polycarbonate, clear
- Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder.
- Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-4/4/S-5/R-R	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-4/4/S-7/R-R	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-4/4/S-10/R-R	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-4/4/S-12/R-R	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-4/4/S-14/R-R	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-4/4/S-25/R-R	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-4/4/S-50/R-R	G	15,250±150(50ft)	Silver	15,250-15,260mm

Unit: mm



Scale	Free				Date	Name	Title
TOLERANCE					Drawn	27.06.13	Wilson
X.	±X				Approved	27.06.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name	Replace <span style="float: right;">rev00</span>	



Title		Modular cable - Straight/Reversed	
		4P4C 50µ", 26AWG, Silver, 5-50 feet	
ASSMANN WSW-No.		AT-S-26-4/4/S-xx/R-R	
Drawing-No.			
Sheet		1/1	