


D-subminiature shielding gaskets

VERY CONFORMABLE TO IRREGULAR SURFACES. Eliminates any gap problem between connector and I/O surface plates. Compresses from .100" to .025" (2,5 to 0,6mm). Outside conductive surface is metalized CuNi fabric at 0.005 to 0.010Ω/lin.in. surface resistivity. Five sizes up to 50-conductors.



PART No.	Conductors	A		B		C		D		E		F		G	
SG140009DS	9 Pin	1.40	35,6	.98	24,9	.78	19,8	.44	11,2	.22	5,6	.70	17,8	.100	2,5
SG175015DS	15 Pin	1.75	44,5	1.31	33,3	1.11	28,2	.44	11,2	.22	5,6	.70	17,8	.100	2,5
SG228025DS	25 Pin	2.28	57,9	1.85	47,0	1.65	41,9	.44	11,2	.22	5,6	.70	17,8	.100	2,5
SG293037DS	37 Pin	2.93	74,4	2.50	63,5	2.29	58,2	.44	11,2	.22	5,6	.70	17,8	.100	2,5
SG284050DS	50 Pin	2.84	72,1	2.41	61,2	2.20	55,9	.55	14,0	.28	7,1	.80	20,3	.100	2,5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[LeaderTech:](#)

[SG140009DS](#) [SG175015DS](#) [SG228025DS](#) [SG284050DS](#) [SG293037DS](#)