

TECHNICAL DATA
DATA SHEET 682, REV -
Formerly part number SHD2199

HERMETIC POWER MOSFET P-CHANNEL

FEATURES:

- -100 Volt, 0.2 Ohm, -18A MOSFET
- Electrically Isolated Hermetically Sealed
- Low $R_{DS(on)}$
- Equivalent to IRF9140 Series

MAXIMUM RATINGS

ALL RATINGS ARE AT $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE SPECIFIED.


RATING	SYMBOL	MIN.	TYP.	MAX.	UNITS
GATE TO SOURCE VOLTAGE	V_{GS}	-	-	± 20	Volts
CONTINUOUS DRAIN CURRENT $V_{GS}=10\text{V}, T_C=25^\circ\text{C}$ $V_{GS}=10\text{V}, T_C=100^\circ\text{C}$	I_D	-	-	-18 -11	Amps
PULSED DRAIN CURRENT @ $T_C=25^\circ\text{C}$	I_{DM}	-	-	-72	Amps
OPERATING AND STORAGE TEMPERATURE	T_{OP}/T_{STG}	-55	-	+150	$^\circ\text{C}$
TERMAL RESISTANCE JUNCTION TO CASE	$R_{\theta JC}$	-	-	0.78	$^\circ\text{C/W}$
TOTAL DEVICE DISSIPATION @ $T_C=25^\circ\text{C}$	P_D	-	-	160	Watts

ELECTRICAL CHARACTERISTICS

DRAIN TO SOURCE BREAKDOWN VOLTAGE $V_{GS} = 0\text{V}, I_D = 1.0\text{mA}$	BV_{DSS}	-100	-	-	Volts
DRAIN TO SOURCE ON STATE RESISTANCE $V_{GS} = -10\text{V}, I_D = -11\text{A}$ $V_{GS} = -10\text{V}, I_D = -18\text{A}$	$R_{DS(ON)}$	-	-	0.20 0.22	Ω
GATE THRESHOLD VOLTAGE $V_{DS} = V_{GS}, I_D = -250\mu\text{A}$	$V_{GS(th)}$	-2.0	-	-4.0	Volts
FORWARD TRANSCONDUCTANCE $V_{DS} \geq -15\text{V}, I_{DS} = -11\text{A}$	g_{fs}	6.2	-	-	$\text{S}(1/\Omega)$
ZERO GATE VOLTAGE DRAIN CURRENT $V_{DS} = 0.8 \times \text{Max. Rating}, V_{GS} = 0\text{V}$ $V_{DS} = 0.8 \times \text{Max. Rating}$ $V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$	I_{DSS}	-	-	-25 -250	μA
GATE TO SOURCE LEAKAGE FORWARD $V_{GS} = -20\text{V}$ GATE TO SOURCE LEAKAGE REVERSE $V_{GS} = 20\text{V}$	I_{GSS}	-	-	-100 100	nA
TOTAL GATE CHARGE $V_{GS} = -10\text{V}$	Q_g	31	-	60	nC
GATE TO SOURCE CHARGE $V_{DS} = \text{Max. Rating} \times 0.5$	Q_{gs}	3.7	-	13	
GATE TO DRAIN CHARGE $I_D = -18\text{A}$	Q_{gd}	7.0	-	35.2	
TURN ON DELAY TIME $V_{DD} = -50\text{V},$ RISE TIME $I_D = -11\text{A},$	$t_{d(on)}$ t_r	-	-	35 85	nsec
TURN OFF DELAY TIME $R_G = 9.1\Omega$ FALL TIME	$t_{d(off)}$ t_f	-	-	85 65	
DIODE FORWARD VOLTAGE $T_J = 25^\circ\text{C}, I_S = -18\text{A},$ $V_{GS} = 0\text{V}$	V_{SD}	-	-	-4.2	Volts
DIODE REVERSE RECOVERY TIME $T_J = 25^\circ\text{C},$ REVERSE RECOVERY CHARGE $I_F = -18\text{A},$ $di/dt = -100\text{A}/\mu\text{sec},$ $V_{DD} \leq -50\text{V}$	t_{rr} Q_{rr}	-	-	280 3.6	nsec μC
INPUT CAPACITANCE $V_{GS} = 0\text{V},$ OUTPUT CAPACITANCE $V_{DS} = 25\text{V},$ REVERSE TRANSFER CAPACITANCE $f = 1.0\text{MHz}$ DRAIN TO CASE CAPACITANCE	C_{iss} C_{oss} C_{rss} C_{DC}	-	1400 600 200 12	-	pF

**SENSITRON
DATA SHEET 682
REVISION -**

MECHANICAL DIMENSIONS: in Inches / mm



LCC-3P

PINOUT TABLE

DEVICE TYPE	PIN 1	PIN 2	PIN 3
MOSFET LCC-3P PACKAGE	DRAIN	SOURCE	GATE

TECHNICAL DATA

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.