



Tel: +44 118 979 1238 Fax: +44 118 979 1283 Email: info@actcrystals.com

70 MHz Standard Filter for Base Station application. Part Number ACTF070053/PK11

Typical Performance



Horizontal: 2.5MHz/Div Vertical: 10dB/Div



Horizontal: 2.5MHz/Div Vertical: 50nsec/Div

Issue: 1 C1

Date: SEPT 04

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Centre Frequency	MHz	69.9	70.0	70.1
Insertion Loss at F ₀	dB		28	
1 dB Bandwidth	MHz		4.78	
3 dB Bandwidth	MHz		5.50	
40dB Bandwidth	MHz		7.16	
Passband Variation	dB		0.60	
Phase Linearity	Deg			
Group Delay Variation	nsec		50	
Absolute Delay	usec		1.4	
Ultimate Rejection	dB		45	
Substrate Material	_		LiTaO3	
Ambient Temperature	°C		25	

In keeping with our ongoing policy of product evolvement and improvement, the above specification is subject to change without notice.

ISO9001: 2000 Registered - Registration number 6830/2

For quotations or further information please contact us at: 3 The Business Centre, Molly Millars Lane, Wokingham, Berks, RG41 2EY, UK





Tel: +44 118 979 1238 Fax: +44 118 979 1283 Email: info@actcrystals.com

Issue: 1 C1

Date: SEPT 04

Package





No Matching Required Source/Load Impedance=50ohm Package Style XI

i CAUTION: Electrostatic Sensitive Device. Observe precautions for handling!

- Unless noted otherwise, all measurements are made with the filter installed in the specified test fixture
 that is connected to a 50Ω test system with VSWR ≤1.2:1. The test fixture L and C are adjusted for
 minimum insertion loss at the filter centre frequency, f_C. Note that insertion loss, bandwidth, and
 passband shape are dependent on the impedance matching component values and quality.
- 2. Unless noted otherwise, specifications apply over the entire specified operating temperature range.
- 3. The specifications of this device are based on the test circuit shown above and subject to change or obsolescence without notice.
- 4. All equipment designs utilizing this product must be approved by the appropriate government agency prior to manufacture or sale.
- 5. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.

In keeping with our ongoing policy of product evolvement and improvement, the above specification is subject to change without notice.